
## metalphoto<sup>\*</sup>


# AIRCRAFT & AEROSPACE













# EXCEPTIONALLY DURABLE. WIDELY SPECIFIED. PHOTOGRAPHIC RESOLUTION.

For over 50 years, the United States Department of Defense has specified Metalphoto photosensitive anodized aluminum for durable labels, nameplates, schematics and control panels installed in harsh operating environments.

The United States Navy frst adopted Metalphoto in 1958 for shipboard labels, placards and damage control signs. Since then, Metalphoto has been incorporated into several major Army weapons systems including the Abrams Tank, the Bradley Fighting Vehicle and the HMMWV. Both Marine Corps and Army Depots operate Metalphoto production facilities. All Departments utilize Metalphoto for Item Unique Identification (IUID) barcode labels as specified under MIL-STD-130.

When durability matters, specify Metalphoto.

#### PRODUCT BENEFITS

#### **EXCEPTIONALLY DURABLE:**

- + UV-stable image is permanently sealed within the anodized aluminum.
- + Virtually impervious to chemicals, heat, abrasion, salt spray and sunlight.
- + Certifed for 20 year plus outdoor application.
- + Earned more top scores than any other IUID barcode label material tested by the U.S. Navy (NSWC, Corona Division, IUID Center; August 2011).

#### **WIDELY SPECIFIED:**

- + Meets a wide array of commercial, government and military specifications.
- + Notable certifications include: MIL-STD-130N, STANAG 2290, GGP-455B(3) Type I, MIL-DTL-15024F, MIL-P-19834B and A-A-50271.

#### PHOTOGRAPHIC RESOLUTION:

- + Photographic image affords extreme detail and contrast at any size.
- + Anti-counterfeit security printing is available.



2284 So. West Temple Salt Lake City, UT 84115 USA T: 1-800-438-0480 F: 1-800-291-6265 E: sales@winmarkinc.com www.winmarkstampandsign.com



### PRODUCT SPECIFICATIONS

#### PERFORMANCE CHARACTERISTICS

Because of its ability to perform across a range of challenging environments, Metalphoto meets an array of government, industrial and military specifications.

CHARACTERISTIC	R E S U LT
Abrasion Resistance	No pronounced image loss, degradation or reduced readability after 7,000 cycles on an abrading wheel.
Acid Corrosion	No deterioration or image degradation after 24 hours in 3% nitric acid.
Heat Resistance	No legibility loss or degradation when subjected to 1,000°F.
Salt Spray Corrosion	No deleterious efect after a 720-hr salt spray (fog) test. 2,6 "Very Good" corrosion resistance after 113 days seawater exposure.
Accelerated Light and Weather Resistance	No pronounced deterioration of legibility after 400-hr carbon arc weatherometer exposure. (≈ 20+ year outdoor life)
Accelerated Oxygen Aging	No discoloration or fading after 96-hr/300 psi/ 70°C oxygen bomb aging
Stain Resistance	No black fading when plates are exposed to tincture of iodine.
Cleaning Resistance	No deleterious efects when tested with alkaline cleaners (MILC- 87937 or equivalent) for aircraft surfaces.
Low Temperature Resistance	No deleterious efect or image fade after 1 hour at -50°F. No impairment of legibility upon exposure at -67°F.
Organic Solvent Resistance	No softening, staining or noticeable fade after 24-hr exposure to: JP-4 fuel, Gasoline, Mineral Spirits, Methyl Ethyl Ketone, Turpentine, Turbine & Jet Fuel, Kerosene, Xylol, Acetone, Toluol, Heptan Trichlorethylene, MIL-H-5606 Hydraulic Fluid and MIL-L-7808 Jet Engine Oil.
Fungus Resistance	Visual reading of "0" per ASTM-G21.
Thermal Shock	No deterioration after 3 cycles between -65°C and 125°C
Moisture Resistance	No deterioration after 10 humidity cycles per MIL-STD-202, method 106.

#### TECHNICAL SPECIFICATIONS

MATERIAL: Anodized Aluminum Sheets

**SIZES:** 10" x 12", 12" x 20"

**THICKNESSES:** .003", .005", .008", .012", .020", .032", .039", .063", .090", .125"

FINISHES:



**MATTE** non-reflective with dull finish



**SATIN** semi-gloss medium reflective material



#4
brushed to resemble
a stainless steel finish



**GLOSS**highly reflective,
mirror-like

# TO ORDER Call 1-800-438-0480 or visit our website at winmarkstampandsign.com

\*Winmark Inc. does not warrant the performance of its materials in any environment.

Metalphoto is a registered trademark of Horizons Incorporated.

